

**TECHNICAL specifications
of concrete wall slates**

Urbi et Orbi established in Greece
Thessalonikis 61 – 18233 Athens
VAT: 076200106
T. 0030 210 4520178
Email. info@urbietorbi.gr
Web. www.urbietorbi.gr
copyright 2014



NUDUS

“NUDUS” concrete tiles are the impression of a concrete wall, molded with building boards (shuttering).



The dimensions of the tile are 100X10X1cm.

Its weight is 2.3 kg with variation +- 10% between the pieces.

It is available in grey color with various grades of hue in every piece, as well as between the pieces. None “NUDUS” tile is identical to another.

They are greatly relief. The 10 mm are the basis of thickness, while at several points the thickness reaches 16 mm

There is +-2mm variation in thickness. There are small differences regarding the length and the width up to 0.5% and it is not considered to be a deficiency or a defect of production, in accordance with the provisions of the conformity with the following standard: EN 492: 2012

The tiles we construct are not produced with the traditional methods of construction, such as pressed or extruded , any they are not baked in oven, as the ceramic ones. Their production is hand-made and made through casting on a vibrating table, while their maturation is effectuated in natural environment. The result of this procedure is the difference between them.

The above capacities of the tiles, as well as the fact that the tiles are made of concrete render them heavier than common ceramic ones, thus being special regarding their placement.

Their placement may be made as for the common tiles by experienced crew and only. However, due to their weight, we suggest to pay attention during their placement so as not to occur slip.

We suggest you to leave a small joint 1-3 mm between the tiles, especially for exterior spaces.

The grouting of the joints is not necessary, but if you want it you may do it with dark grey joint grout of your choice. You’d better use a caulking gun. We suggest you to use a brush or a sponge for the finish of the filling so as to offer you natural result. You



may choose grout with similar color to the color of the tiles and create more relief effect in the joints. Thus you will have a more natural result. Clean immediately the residues of glue or grout. For further information regarding the transfer, storage, placement of the tiles you may see the



general instructions leaflet.

The tiles are delivered by us, upon your choice, protected with impregnation of HYDROREP material of FILA. However, for exterior walls you suggest you a further coating of FILAFOB after the placement for protection from oils and graffiti.

Cracks or breaks are defects of the product, however the strict control of quality and the package excludes any possibility of our fault. They may result due to the transfer, therefore we suggest you to fully control your receipts.

Do not stack the "NUDUS" tiles. Follow the instructions of the general instructions leaflet and of the package. The tiles must be carefully taken off the package and be placed on a horizontal surface with the direction the arrows of the package show (the width of the tile at a vertical position) and not the one on the other.

MECHANICAL PROPERTIES

(Average values from 4x4x16 cm
specimens water-cured at 20°C)

Compressive strength 100 MPa

Bending strength 9 MPa

Water porosity untreated 2,3%

Urbi et Orbi established in Greece, Thessalonikis 61-18233 Athens- VAT: 076200106

T. 0030 210 4520178

Email. info@urbietorbi.gr

Web. www.urbietorbi.gr

The technical data sheet was drawn up on the basis of our better techniques and applied know-how. However, we are not able to directly intervene to the conditions of each plant and the execution of the works, thus this information is general suggestions and in no way do they bind our Company.

Hence, we suggest you an advance trial in order to verify the suitability of the product for the provided use.

